#### SAFETY DATA SHEET

**ASMC** 

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY



ArcusStone<sup>®</sup>

ArcusStone Products, LLC 180 Harbor Drive, Suite 200. Sausalito, CA. 94965

Arcus Marblecoat TRADE NAME: **CHEMICAL FAMILY:** Cement based aggregate MAIN USE: Aggregate for specialty coating

Page 1 of 6

**EMERGENCY TELEPHONE NUMBER:** 415-339-4060

#### **SECTION 2: HAZARDS IDENTIFICATION**

#### **GLOBALLY HARMONIZED SYSTEM (GHS)**

**CLASSIFICATION: HAZARDOUS CARCINOGENICITY: CATEGORY 1A SKIN CORROSION:** CATEGORY 1A **EYE DAMAGE: CATEGORY 1** 

**SKIN SENSITIZATION: SUB-CATEGORY 1B** 

### **GHS LABEL ELEMENTS HAZARD PICTOGRAMS**







**SIGNAL WORD: DANGER!** 

## **HAZARD STATEMENTS:**

H314: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE H317: MAY CAUSE AN ALLERGIC SKIN REACTION

H335: MAY CAUSE RESPIRATORY TRACT IRRITATION

H350: MAY CAUSE CANCER

H371: CAUSES DAMAGE TO LUNGS THROUGH PROLONGED OR REPEATED EXPOSURE BY INHALATION

## PRECAUTIONARY STATEMENTS:

### **PREVENTION**

P202: DO NOT HANDLE UNTIL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD

P260: DO NOT BREATHE DUST

P270: DO NO EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT

P272: CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED OUT OF THE WORKPLACE P280: WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION

P284: IN CASE OF INADEQUATE VENTILATION WEAR RESPIRATORY PROTECTION

#### **RESPONSE**

P308+P313: IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ATTENTION.

P303+P361+353: IF ON SKIN (OR HAIR): REMOVE/TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/SHOWER

P305+P351+P338: IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO SO. CONTINUE RINSING.

P304+P340 IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHIN

P301+P331: IF SWALLOWED: RINSE MOUTH. DO NOT INDUCE VOMITING

P337+P313: IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION

ASMC Page 2 of 6

P333+P313: IF SKIN IRRITATION OR RASH OCCURS: GET MEDICAL ADVICE/ATTENTION

P361+P364: TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE

P391: COLLECT SPILLAGE

**STORAGE** 

P403+P235: STORE IN A WELL-VENTILATED PLACE. KEEP COOL

**DISPOSAL** 

P501: DISPOSE OF CONTENTS/CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT

# OTHER HAZARDS

NO DATA AVAILABLE

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

HAZARDOUS INGREDIENTS	Wt %	CAS Number
DOLOMITIC LIMESTONE	30-60	001317-65-3
PORTLAND CEMENT	30-60	065997-15-1
CALCIUM HYDROXIDE	1-5	001305-62-0

#### **SECTION 4: FIRST AID MEASURES**

**GENERAL**: IN DRY FORM THE POWDER POSES LITTLE IMMEDIATE HAZARD. EXPOSURE OF SUFFICIENT DURATION TO WET MATERIAL CAN CAUSE TISSUE DAMAGE.

EYES: FLUSH WITH WATER FOR 15 MINUTES. AVOID RUBBING. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

SKIN: WASH WITH MILD SOAP AND WATER. SEEK MEDICAL TREATMENT WITH LONG EXPOSURES TO WET PRODUCT.

**INHALATION**: REMOVE AFFECTED PERSON TO FRESH AIR. SEEK MEDICAL ATTENTION IF COUGHING OR OTHER SYMPTOMS DO NOT SUBSIDE.

**INGESTION**: GIVE 3 – 4 GLASSES OF WATER OR MILK IF PERSON CONSCIOUS. **DO NOT INDUCE VOMITING!** OBTAIN MEDICAL CARE AND TREATMENT.

## **SECTION 5: FIRE FIGHTING MEASURES**

FLASH POINT: NONE CONDITIONS OF FLAMMABILITY: NA

FLAMMABLE LIMITS: <u>LEL:</u> ND <u>UEL:</u> ND

OSHA CLASS: NOT REGULATED AUTO IGNITION TEMP: ND

**HAZARDOUS COMBUSTION PRODUCTS: NONE** 

**SENSITIVITY TO IMPACT: ND** 

SENSITIVITY TO STATIC DISCHARGE: ND

**EXTINGUISHING MEDIA: NA** 

**SPECIAL FIRE FIGHTING PROCEDURES**: NOT IGNITABLE

**UNUSUAL FIRE AND EXPLOSIVE HAZARDS: NA** 

FLASH POINT: NA OSHA CLASS: NONE SHOWN

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** USE DUSTLESS METHODS (VACUUM) AND PLACE IN CLOSABLE CONTAINERS FOR DISPOSAL. SCRAPE UP WET MATERIAL AND PLACE IN CONTAINERS. ALLOW TO DRY BEFORE DISPOSAL. WEAR PROTECTIVE EQUIPMENT AS SHOWN IN SECTION 8.

ASMC Page 3 of 6

### **SECTION 7: HANDLING AND STORAGE**

**GENERAL**: AVOID GENERATING AND BREATHING DUST. USE ONLY WITH ADEQUATE VENTILATION. KEEP CONTAINER CLOSED. WASH THOROUGHLY AFTER HANDLING.

STORAGE: STORE IN COOL, DRY SPACES. HANDLE IN MANNERS WHICH PREVENT DUST.

## **SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION**

### **EXPOSURE LIMITS (ppm)**

INGREDIENTS (CAS)	OSHA TWA STEL	ACGIH TWA STEL	OTHER
001317-65-3	15mg/m³ ND	10mg/m³ ND	Respirable Dust
065997-15-1	10mg/m <sup>3</sup> ND	10mg/m <sup>3</sup> ND	Respirable Dust
001305-62-0	5mg/m <sup>3</sup> ND	5mg/m <sup>3</sup> ND	Respirable Dust

LEGEND: (M) MAX. EXPOSURE LIMIT; (S) OCCUPATIONAL EXP. LIMIT; (R) SUPPLIERS REC. LIMIT, (+) PERCUTANEOUS RISK

NOTE 1: VALUES MEANINGFUL ONLY WHEN HARDENED PRODUCT IS ABRADED, GROUND, ETC.

**RESPIRATORY PROTECTION**: NONE AS REQUIRED. NIOSH-MSHA APPROVED RESPIRATORS (PAPER DISPOSABLE; ½ OR FULL FACE PIECE AIR PURIFYING; SUPPLIED AIR – DEPENDENT UPON PEL LEVELS).

<5X PEL - ANY DUST RESPIRATOR.

5<10X PEL – ANY DUST RESPIRATOR (EXCEPT SINGLE USE OR ¼ MASK). ANY FUME OR HIGH EFFICIENCY PARTICULATE FILTER RESPIRATOR.

10<50X PEL - HIGH EFFICIENCY PARTICULATE FILTER RESPIRATOR WITH FULL FACE PIECE.

50<500X PEL – POWERED AIR-PURIFYING RESPIRATOR WITH PARTICULATE FILTER.

>500X PEL - SELF-CONTAINED BREATHING APPARATUS.

**PROTECTIVE GLOVES: NITRILE RUBBER** 

**EYE PROTECTION**: SPLASH-PROOF GOGGLES OR CHEMICAL SAFETY GLASSES

OTHER PROTECTIVE EQUIPMENT: LONG SLEEVED SHIRTS AND TROUSERS. EMERGENCY SHOWERS AND EYE WASH STATIONS

SHOULD BE READILY ACCESSIBLE.

ENGINEERING CONTROLS: NO SPECIFIC CONTROLS NEEDED. GENERAL AND LOCAL EXHAUST RECOMMENDED.

#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

BOILING POINT: 2230°C (4046°F)

VAPOR PRESSURE: NA

MELTING POINT: NA

MELTING POINT: NA

**VAPOR DENSITY**: NA **EVAPORATION RATE**: NA (AIR = 1) (BUTYL ACETATE = 1)

SOLUBILITY IN WATER: VERY SLIGHT PH: 8-11.5 COEFFICIENT of
WATER/OIL DISTRIBUTION: ND
ODOR THRESHOLD: ND

APPEARANCE AND ODOR: COLORED GRANULAR POWDER, NO DISTINCT ODOR.

**% VOLATILES BY VOLUME:** 0% **%SOLIDS BY WEIGHT:** 100%

ASMC Page 4 of 6

#### **SECTION 10: STABILITY AND REACTIVITY**

**STABILITY**: STABLE;

**CONDITIONS TO AVOID: NOT APPLICABLE (MATERIAL IS STABLE)** 

**INCOMPATIBILITY (MATERIAL TO AVOID):** VERY STRONG OXIDIZING AGENTS MAY CAUSE FIRES. AVOID ACIDS AND AMMONIUM SALTS.

**HAZARDOUS DECOMPOSITION PRODUCTS**: WATER PRODUCES HYDRATION AND FORMATION OF CAUSTIC CALCIUM HYDROXIDE.

HAZARDOUS POLYMERIZATION (REACTIVITY): WILL NOT OCCUR.

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

LIKELY ROUTES OF EXPOSURE: EYE CONTACT, SKIN CONTACT, INHALATION, INGESTION.

EYES:

ACUTE - MAY CAUSE IRRITATION OR INFLAMMATION. ABRASIVE TO EYES.

CHRONIC - - REPEATED CONTACT MAY CAUSE CHEMICAL BURNS RESULTING IN CORNEAL DAMAGE

**SKIN CONTACT:** 

**ACUTE** – IRRITATION/DISCOMFORT MAY OCCUR.

CHRONIC - (CAUSTIC) CHEMICAL BURNS CAN OCCUR.

**SKIN ABSORPTION:** 

ACUTE - ND

**CHRONIC** - ND

**INHALATION:** 

**ACUTE** – MAY CAUSE IRRITATION. COUGHING OR SHORTNESS OF BREATH MAY RESULT

**CHRONIC** – PERSISTENT COUGH. SHORTNESS OF BREATH.

INGESTION:

ACUTE - ND

**CHRONIC** - ND

**CONDITIONS AGGRAVATED BY EXPOSURE**: PROLONGED INHALATION OF ANY DUST PARTICULATE MAY AGGRAVATE RESPIRATORY MEDICAL CONDITIONS.

**ACUTE TOXICITY** 

**ACUTE ORAL TOXICITY: ND** 

SKIN CORROSION/IRRITATION

DOT SKIN CORROSION STUDY: CORROSIVE IN ALL RABBITS AT 3 MINUTES EXPOSURE

**SERIOUS EYE DAMAGE/EYE IRRITATION** 

SEVERE EYE IRRITATION

**SENSITIZATION** 

FOR SKIN SENSITIZATION:

MAY CAUSE AN ALLERGIC REACTION AFTER A SINGLE EXPOSURE OR WITH REPEATED OR PROLONGED SKIN CONTACT

FOR RESPIRATORY SENSITIZATION:

NOT CLASSIFIED BUT POSSIBLE DUE TO SKIN SENSITIZATION EFFECT

ASMC Page 5 of 6

## SECTION 11: TOXICOLOGICAL INFORMATION CON'T.

## SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (SINGLE EXPOSURE)

CATEGORY 3, INHALATION AND SKIN CONTACT, RESPIRATORY TRACT IRRITATION, SKIN IRRITATION

### SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (REPEATED EXPOSURE)

CATEGORY 1, INHALATION, RESPIRATORY TRACT

CARCINOGENIC DATA: NTP: YES OSHA: NO IARC: YES (1A)

TERATOGENICITY: ND MUTAGENICITY: ND

EMBRYOTOXICITY: ND SYNERGISTIC MATERIAL: ND

**OVEREXPOSURE EFFECTS**: REPEATED, PROLONGED INHALATION OF EXCESSIVE QUANTITIES OF QUARTZ DUST MAY RESULT IN DELAYED LUNG DISEASE (SILICOSIS). WET CEMENT CAN CAUSE ALKALI BURNS AND DRY THE SKIN. DUST MAY CAUSE EYE AND

NOSE INFLAMMATION.
IRRITANCY: YES
SENSITIZER: YES

## **SECTION 12: ECOLOGICAL INFORMATION**

#### TOXICITY

**ACUTE TOXICITY TO FISH: ND** 

ACUTE TOXICITY TO AQUATIC INVERTEBRATES: ND ACUTE TOXICITY TO ALGAE/AQUATIC PLANTS: ND

**TOXICITY TO BACTERIA: ND** 

PERSISTANCE AND DEGRADABILITY BIOACCUMULATIVE POTENTIAL

BIOACCUMULATION: ND MOBILITY IN SOIL: ND

### **SECTION 13: DISPOSAL CONSIDERATIONS**

WASTE DISPOSAL METHODS: DISPOSE IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS

## **SECTION 14: TRANSPORT INFORMATION**

DOT PROPER SHIPPING NAME: NOT REGULATED HAZARD CLASS: NA

UN NUMBER: NA PACKAGING GROUP: NA

DOT PRODUCT RQ LBS (KGS): NA HAZARD LABEL: NA

**HAZARD PLACARD** NA

**IMO SHIPPING DATA: NOT REGULATED** 

ICAO/IATA SHIPPING DATA: NOT REGULATED

**ADDITIONAL INFORMATION: NONE** 

## SAFETY DATA SHEET

ASMC Page 6 of 6

## **SECTION 15: REGULATORY INFORMATION**

**VOC: COMPONENT** = 0 gms/Liter

AS APPLIED (Part of a multi-component system) = 0gms/Liter

TSCA (TOXIC SUBSTANCE CONTROL ACT): ALL COMPONENTS ARE LISTED IN THE TSCA CHEMICAL SUBSTANCE INVENTORY.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION and LIABILITY ACT): ND

SARA TITLE III

SECTION 312 HAZARD CLASS: HAZARDOUS SUBSTANCE WITH DELAYED HEALTH EFFECTS.

SECTION 313 LISTED INGREDIENTS: NONE ABOVE de Minimus LEVELS

CALIFORNIA PROPOSITION 65: THE BELOW LIST OF COMPOUNDS IS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE

CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM: CAS # 14808-60-7

## **SECTION 16: OTHER INFORMATION**

INITIAL ISSUE DATE: OCTOBER 30, 2017

**HAZARD RATING** 

HMIS: HEALTH 3 FLAMMABILITY 0 REACTIVITY 0

**LEGEND** 

ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS

OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION

STEL: SHORT TERM EXPOSURE LIMIT

TWA: TIME WEIGHTED AVERAGE

PEL: PERMISSIBLE EXPOSURE LIMIT

TLV: THRESHOLD LIMIT VALUE

NA: NOT APPLICABLE

NE: NOT ESTABLISHED

ND: NO DATA

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations and orders.